


GENERAL TOLERANCE:±0.2

LCD Type	3.5" TFT, Transmissive, Normally white, TN
Resolution	320(RGB)*480
View Direction	All OGCLOCK
Driver IC	IL19488
Color Depth	65K
Interface Types	MCUI6-bit
Operating voltage	2.8 V
TP/Lens	Without
Backlight LEDs	6 LEDs, 120mA, 3.2V
Surface luminance	300 cd/m ²
Operating temperature	-20 °C ~ 70 °C
Storage Temperature	-30 °C ~ 80 °C
Storage Humidity	60% ~ 90% max



Pin Assignment	
1	GND
2	IOVCC(1.8V)
3	VCC(2.8V)
4	WR
5	CS
6	RD
7	RS
8	RESET
9	FMARK
10~25	DB0~DB15
26	GND
27	GND
28	NC
29	K
30	NC
31	A
32	NC
33	YD
34	XR
35	TU
36	XL
37	GND
38	NC
39	NC
40	NC

MCU 16位



Need to pay attention to

the key size with *



东莞市一众显示科技有限公司
DONG GUAN TEAM SOURCE DISPLAY TECH. CO, LTD.

版本 (Version)	变更日期 (Change History)	日期 (Date)	视角 (View):	比例 (Proportion):	设计 (DESIGN)	审核 (AUDITING)	批准 (APPROVED)
V1			单位 (Unit):	页 面 (Page):	1 / 1		
V2			产品型号 (Product Type)	版本 (Version)	TST035HVQI-45	2018.8.8	