



PI stiffening plate



CURRENT IF=60mA
20*3=60mA

	PIN NAME
1	LED-K
2	LED-A
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	DCLK
31	DISP
32	HSYNC
33	VSYNC
34	DEN
35	NC
36	GND
37	XR(NC)
38	YD(NC)
39	XL(NC)
40	YU(NC)

LCD Type	7.0" TFT, Transmissive, Normally white, TN
Resolution	800(RGB)*480
View Direction	12 O'CLOCK
Driver IC	EK9716BD/BD3&EK73002ACGB
Color Depth	16.7M
Interface Types	RGB 24Bit
Operating voltage	3.3V
TP/Lens	Without
Backlight LEDs	21 LEDs, 60mA, 22.4V
Surface luminance	450(min.), 500(Typ) cd/m ²
Operating temperature	-20 °C ~ 70 °C
Storage Temperature	-30 °C ~ 80 °C
Storage Humidity	60°C 90% max

" " Need to pay attention to the key size with *				东莞市一众显示科技有限公司 DONG GUAN TEAM SOURCE DISPLAY TECH. CO, LTD.			
版本 (Version)	变更记录 (Change History)	日期 (Date)	视角 (View):	比例 (Proportion):	设计 (DESIGN)	审核 (AUDITING)	批准 (APPROVED)
V1			⊕	1 : 1	Jacky	Aron	
V2			MM	1 / 1	2018.6.8	2018.6.8	
			产品型号 (Product Type):	TST070WVBE-32			
			图纸版本 (Version):	V1			