




A



FHI2-32S-0.5SH
PIN Definition

Pin	Symbol
1	(GND)
2	VCC (5.0V)
3	BL_EN
4	RS
5	WR
6	RD
7	DB0
8	DB1
9	DB2
10	DB3
11	DB4
12	DB5
13	DB6
14	DB7
15	DB8
16	DB9
17	DB10
18	DB11
19	DB12
20	DB13
21	DB14
22	DB15
23	NC
24	NC
25	CS
26	RESFT
27	NC
28	NC
29	NC
30	NC
31	NC
32	DISP/NC



CURRENT: IF=20*2=40mA, 15.5V (REF.)

BL_EN: High, Backlight ON;
Low, Backlight OFF.

All I/O port operating voltage is 3.3V.

由 Autodesk 教育版产品制作

LCD type	4.3" TFT, Transmissive, Normally white, TN
Resolution	480 (RGB) * 272
View direction	12.0° clock
Driver IC	SS91963
Color Depth	65K/262K/16.7M
Interface Types	Mini 501 (F/18bit)
Operating voltage	VCC=5.0V I/OVCC=3.3V
TP/Lens	With RTP
Backlight LEDs	10 LEDs
Surface luminance	240lm/m ² , 280cp/cd/m ²
Operating temperature	-20 °C ~ 70 °C
Storage temperature	-30 °C ~ 80 °C
Storage Humidity	60% C 90% max

版本 (Version)	变更记录 (Change History)	日期 (Date)	视角 (View):	比例 (Proportion):	设计 (DESIGN)	审核 (AUDITING)	批准 (APPROVED)
A0	INITIAL RELEASE	Apr-3-2019	M M	1:1			
A1				±0.2			
A2				TSM0431WQBS-35P			

东莞市一众显示科技有限公司
DONG GUAN TEAM SOURCE DISPLAY TECH. CO, LTD.

由 Autodesk 教育版产品制作

5

6

1

2

3

4

5

6