


No:	PIN NAME
1	Y+ (YU)
2	X+ (XR)
3	Y- (YD)
4	X- (XL)
5	BL-A
6	BL-K
7	GND
8	VDD
9	NC
10	NC
11	CS
12	RESET
13	RS
14	WR
15	RD
16	DB7
17	DB6
18	DB5
19	DB4
20	DB3
21	DB2
22	DB1
23	DB0
24	GND

PIN	WIRING
1	YU
2	XL
3	YD
4	XR

TP Logic



LCD Type	1.44" TFT, Transmissive, Normally white, TN
Resolution	128*(RGB)*128
View Direction	12 O'CLOCK
Driver IC	ST7735S
Color Depth	65K/262K
Interface Types	MCU8-bit
Operating voltage	VDD=2.8V~3.3V
With/without TP	With RTP
Backlight LEDs	2 LEDs, 40mA, 3.2V
Operating temperature	-20 C° ~ 70 C°
Storage Temperature	-30 C° ~ 80 C°
Storage Humidity	10RH ~ 40RH

"👉" Need to pay attention to size		"*" As the focus control size		东莞市一众显示科技有限公司 DONG GUAN TEAM SOURCE DISPLAY TECH. CO, LTD.			设计 (DESIGN)	审核 (AUDITING)	批准 (APPROVED)
版本 (Version)	变更记录 (Change History)	日期 (Date)	视角 (View):	比例 (Proportion):	1 : 1	设计 (DESIGN)	审核 (AUDITING)	批准 (APPROVED)	
V1			单位 (Unit):	MM	页面 (Page):				1 / 1
V2			产品型号 (Product Type):	TST144QQCS-01P					
V3			版本 (Version):	V0					