



CURRENT IF=60mA
20*3=60mA

	PIN NAME
1	LED-K
2	LED-A
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	DCLK
31	DISP
32	HSYNC
33	VSYNC
34	DN
35	NC
36	GND
37	XR (NC)
38	YD (NC)
39	XL (NC)
40	YU (NC)

LCD Type	7.0" TFT, Transmissive, Normally white, TN
Resolution	800(RGB)*480
View Direction	12 O'CLOCK
Driver IC	EK9716BD/BD3&EK73002ACGB
Color Depth	16.7M
Interface Types	RGB 24Bit
Operating voltage	3.3V
TP/Lens	With RTP
Backlight LEDs	21 LEDs, 60mA, 22.4V
Surface luminance	380~420 cd/m2
Operating temperature	-20 °C~70 °C
Storage Temperature	-30 °C~80 °C
Storage Humidity	60°C 90% max

" " Need to pay attention to		the key size with *		TSD		东莞市一众显示科技有限公司 DONG GUAN TEAM SOURCE DISPLAY TECH. CO, LTD.		
版本 (Version)	变更记录 (Change History)	日期 (Date)	视角 (View):	比例 (Proportion):	1 : 1	设计 (DESIGN)	审核 (AUDITING)	批准 (APPROVED)
V1			单位 (Unit):	M M	1 / 1			
V2			产品型号 (Product Type):	TST070WVBE-32P		Jacky	Aron	
			图纸版本 (Version):	V1		2018.6.8	2018.6.8	