



深圳市一众显示科技有限公司

SHEN ZHEN TEAM SOURCE DISPLAY TECH. CO, LTD.

TFT-LCD Module Specification

Module NO.: TST35HV15BR

Version: V1.0

APPROVAL FOR SPECIFICATION

APPROVAL FOR SAMPLE

| | |
|------------------------------------|----------------|
| For Customer' s Acceptance: | |
| Approved by | Comment |
| | |

| | | |
|-----------------------------|--------------------|---------------------|
| Team Source Display: | | |
| Presented by | Reviewed by | Organized by |
| | | |

| Version No. | Date | Content | Remark |
|-------------|-----------|-----------------|--------|
| V1.0 | 2017-7-10 | Initial Release | |
| | | | |

| ITEM | Specification | Unit |
|--------------------------------|--|-------------------|
| LCD Type | a-Si TFT, Transmissive, Normally white, TN | - |
| LCD Size | 3.5 | inch |
| Resolution (W x H) | 320 x (RGB) x 480 | pixel |
| LCM (W x H x D) | 54.5(W) x 83.0(H) x 3.6(D) | mm |
| Active Area (W x H) | 48.96 (W) x 73.44 (H) | mm |
| Dot Pitch (W x H) | 0.153 x 0.153 | mm |
| Viewing Direction | 12 o'clock | - |
| Gray Scale Inversion Direction | 6 o'clock | - |
| Viewing Angle | Top:45, Bottom:35; Left/ Right:55 | deg. |
| Color Depth | 65K/262K | - |
| Pixel Arrangement | RGB-stripe | - |
| Backlight Type | 6 LEDs | - |
| Surface Luminance | 228 | cd/m ² |
| Surface Treatment | Anti-Glare | - |
| Driver IC | ILI9488 | - |
| Interface Type | MCU 8/16-bit | - |
| Input Voltage | 2.8 | V |
| With/Without TP | Resistive Touch Panel | - |
| Weight | 28 | g |

Note 1: RoHS compliant

Note 2: LCM weight tolerance: ± 5%.

CONTENTS

1 PRODUCT DRAWINGS----- 3 -

2 INTERFACE DESCRIPTION----- 4 -

3 LCM INTERFACE TIMING----- 5 -

 3.1 RESET TIMING----- 5 -

 3.2 MCU READ/WRITE TIMING----- 5 -

4 INITIAL CODE----- 6 -

5 ABSOLUTE MAXIMUM RATINGS----- 9 -

6 ELECTRICAL CHARACTERISTICS----- 9 -

7 BACKLIGHT CHARACTERISTICS----- 9 -

8 LCD OPTICAL SPECIFICATIONS----- 10 -

9 TOUCH PANEL SPECIFICATIONS----- 12 -

10 RELIABILITY TEST----- 12 -

11 INSPECTION STANDARDS----- 13 -

 11.1 VISUAL INSPECTION CRITERION IN COSMETIC----- 13 -

 11.1.1 Glass defect----- 13 -

 11.1.2 LCM appearance defect----- 13 -

 11.1.3 FPC----- 14 -

 11.1.4 Black tape----- 14 -

 11.1.5 Silicon----- 14 -

 11.1.6 Touch Panel----- 14 -

 11.2 VISUAL INSPECTION CRITERION IN ELECTRICAL DISPLAY----- 15 -

 11.3 OTHERS----- 16 -

12 SUGGESTIONS FOR USING LCD MODULES----- 16 -

 12.1 HANDLING OF LCM----- 16 -


 12.2 STORAGE----- 17 -

2 Interface description

| PIN NO. | Symbol | description |
|---------|-------------|--|
| 1 | GND | System Ground. (0V) |
| 2 | GND | System Ground. (0V) |
| 3 | IM0 | IM0=0: MCU16-BIT, DB0~DB15 IM0=1: MCU8-BIT, DB0~DB7 |
| 4 | FMARK | Tearing Effect output signal |
| 5 | YD | The touch panel Y Down pin |
| 6 | XL | The touch panel X Left pin |
| 7 | RESET | Reset input signal |
| 8 | RS | Data/Command Selection pin |
| 9 | CS | Chip select signal. |
| 10 | RD | read signal |
| 11 | WR | serves as a write signal |
| 12 | VCC | Power supply +2.8V |
| 13 | NC | |
| 14 | GND | System Ground. (0V) |
| 15~24 | DB15~DB6 | Data BUS |
| 25~30 | DB0~DB5 | Data BUS |
| 31 | YU | The touch panel Y Up pin |
| 32 | XR | The touch panel X Right pin |
| 33 | LEDA | Backlight A Aothod input pin. |
| 34~39 | LEDK1~LEDK6 | Backlight K Cathode input pin. |
| 40 | GND | System Ground. (0V) |

3 LCM Interface Timing

3.1 Reset Timing




| Signal | Symbol | Parameter | Min | Max | Unit |
|--------|--------|-----------------------|-------------|-----|------|
| NRESET | tRESW | Reset low pulse width | 10 | - | us |
| | tREST | Reset complete time | 5 (note 1) | - | ms |
| | | | 120(note 2) | - | ms |

Note: (1) When reset applied during SLPIN mode;

(2) When reset applied during SLPOUT mode.

3.2 MCU Read/Write Timing




(VSSA=0V, VDD1=1.8V, VDD3=2.8V, TA=25°C)

| Signal | Symbol | Parameter | min | max | Unit | Description |
|----------|--------|---|-----|-----|------|---|
| DCX | tAST | Address setup time | 0 | - | ns | - |
| | tAHT | Address hold time (Write/Read) | 10 | - | | |
| CSX | tCS | Chip select setup time (Write) | 10 | - | ns | - |
| | tRCS | Chip select setup time (Read register) | 45 | - | | |
| | tRCSFM | Chip select setup time (GRAM) | 355 | - | | |
| | tCSF | Chip select wait time (Write/Read) | 10 | - | | |
| WRX_SCL | tWC | Write cycle (write register) | 50 | - | ns | - |
| | tWC | Write cycle (write GRAM@SLPOUT) | 47 | - | | |
| | tWC | Write cycle (write GRAM@SLPIN) | 100 | - | | |
| | tWRH | Control pulse "H" duration | 15 | - | | |
| | tWRL | Control pulse "L" duration | 15 | - | | |
| RDX | tRC | Read cycle (read register) | 160 | - | ns | - |
| | tRC | Read cycle (GRAM) | 450 | - | | |
| | tRDH | Control pulse "H" duration | 90 | - | | |
| | tRDL | Control pulse "L" duration(read register) | 35 | - | | |
| | tRDL | Control pulse "L" duration(GRAM) | 345 | - | | |
| DB[23:0] | tDST | Data setup time | 10 | - | ns | For maximum CL=30pF For minimum CL=8pF |
| | tDHT | Data hold time | 10 | - | | |
| | tRAT | Read access time(read register) | - | 40 | | |
| | tRAT | Read access time(GRAM) | - | 340 | | |
| | tODH | Output disable time | 20 | 80 | | |

Note: The input signal rise time and fall time (tr, tf) is specified at 15 ns or less.

Logic high and low levels are specified as 30% and 70% of VDD1 for Input signals.



4 INITIAL CODE

```

LCD_REST=0;// Hardware reset
Delayms(15);
LCD_REST=1;
Delayms(120);

write_reg(0xB9); //SET password
write_dat(0xFF);
write_dat(0x83);
write_dat(0x57);
    
```

```

write_reg(0xB1); //SETPower
write_dat(0x00); //STB
write_dat(0x11); //VGH = 15V, VGL = -10V
write_dat(0x1E); //VSPR = 4.5V
write_dat(0x1E); //VSNR = -4.5V
write_dat(0xC3); //AP
write_dat(0x77); //FS

write_reg(0xB4); //SETCYC
write_dat(0x11); //I-dot
write_dat(0x40); //RTN
write_dat(0x00); //DIV
write_dat(0x2A); //N_DUM
write_dat(0x2A); //I_DUM
write_dat(0x20); //GDON
write_dat(0x78); //GDOFF

write_reg(0xB6); //VCOMDC
write_dat(0x33);

write_reg(0xC0); //SETSTBA
write_dat(0x70); //N_OPON
write_dat(0x70); //I_OPON
write_dat(0x00); //STBA
write_dat(0x3C); //STBA
write_dat(0xC4); //STBA
write_dat(0x08); //GENON

write_reg(0xC2); // Set Gate EQ
write_dat(0x00);
write_dat(0x08);
write_dat(0x04);

write_reg(0xCC); //Set Panel
write_dat(0x09); //SS_Panel = 1, BGR_Panel = 1

write_reg(0xE0); //Set Gamma
write_dat(0x00); //VRP0
write_dat(0x05); //VRP1
write_dat(0x12); //VRP2
write_dat(0x21); //VRP3
write_dat(0x2C); //VRP4
write_dat(0x40); //VRP5
write_dat(0x4B); //VRP6

```

```
write_dat(0x52); //VRP7
write_dat(0x47); //VRP8
write_dat(0x41); //VRP9
write_dat(0x3A); //VRP10
write_dat(0x31); //VRP11
write_dat(0x2E); //VRP12
write_dat(0x29); //VRP13
write_dat(0x24); //VRP14
write_dat(0x00); //VRP15
write_dat(0x00); //VRN0
write_dat(0x05); //VRN1
write_dat(0x12); //VRN2
write_dat(0x21); //VRN3
write_dat(0x2C); //VRN4
write_dat(0x40); //VRN5
write_dat(0x4B); //VRN6
write_dat(0x52); //VRN7
write_dat(0x47); //VRN8
write_dat(0x41); //VRN9
write_dat(0x3A); //VRN10
write_dat(0x31); //VRN11
write_dat(0x2E); //VRN12
write_dat(0x29); //VRN13
write_dat(0x24); //VRN14
write_dat(0x00); //VRN15
write_dat(0x01); //GMA_Reload

write_reg(0x3A); //COLMOD
write_dat(0x55); //RGB565
write_reg(0x11); //Sleep Out
Delayms(150);
write_reg(0x29); //Display On
```

5 Absolute Maximum Ratings

| PARAMETER | SYMBOL | MIN | MAX | UNIT |
|---------------------------|-----------|------|----------------|------|
| Supply Voltage (Analog) | VCC~GND | -0.3 | 4.6 | V |
| Logic signal voltage(I/O) | IOVCC~GND | -0.3 | 4.6 | V |
| Operating Temperature | TOP | -20 | 70 | ° C |
| Storage Temperature | TST | -30 | 80 | ° C |
| Humidity | RH | - | 90%(Max 60° C) | RH |

6 Electrical Characteristics

| PARAMETER | SYMBOL | MIN | TYP | MAX | UNIT |
|----------------------------|--------|----------|-----|----------|------|
| Analog operating voltage | VCC | 2.5 | 2.8 | 3.3 | V |
| Logic operating voltage | IOVCC | 1.65 | 1.8 | 3.3 | V |
| Input Current | IDD | - | TBD | - | mA |
| Input Voltage ' H ' level | VIH | 0.7IOVCC | - | IOVCC | V |
| Input Voltage ' L ' level | VIL | GND | - | 0.3IOVCC | |
| Output Voltage ' H ' level | VOH | 0.8IOVCC | - | IOVCC | |
| Output Voltage ' L ' level | VOL | GND | - | 0.2IOVCC | |

7 Backlight Characteristics

| ITEM | SYMBOL | MIN | TYP | MAX | UNIT |
|---------------------------|-----------------|-------|-------|-----|------|
| Voltage for LED backlight | V _f | - | 3.2 | 3.4 | V |
| Current for LED backlight | I _f | - | 120 | - | mA |
| Power consumption | W _{bl} | - | 384 | - | mW |
| Uniformity | Avg | 80 | - | - | % |
| LED Life Time | - | 30000 | 40000 | - | Hrs |

Note:

1. The LED life time is defined as the module brightness decrease to 50% original brightness at Ta=25°C, 60%RH ±5 %.
2. The life time of LED will be reduced if LED is driven by high current, high ambient temperature and humidity conditions.
3. Typical operating life time is an estimated data.
4. Permanent damage to the device may occur if maximum values are exceeded or reverse voltage is loaded .Functional operation should be restricted to the conditions described under normal operating conditions.

8 LCD Optical specifications

With Resistive touch panel

| Item | Symbol | Condition | Specification | | | Unit | Remark |
|---|--------|----------------------|---------------|-------|-------|-------------------|------------|
| | | | Min | Typ | Max | | |
| Response time (By Quick) | Tr+Tf | $\theta = 0^\circ$ | - | 20 | 40 | ms | Note 5 |
| Contrast ratio | CR | $\theta = 0^\circ$ | - | 500 | - | | Note 2,6 |
| Viewing angle | Top | $CR \geq 10$ | - | 45 | - | Deg. | Note 2,6,7 |
| | Bottom | $CR \geq 10$ | - | 35 | - | | |
| | Left | $CR \geq 10$ | - | 55 | - | | |
| | Right | $CR \geq 10$ | - | 55 | - | | |
| Color chromaticity (CF only with ITO, light source is C light, CIE 1931) | Wx | $\theta = 0^\circ$ | 0.292 | 0.307 | 0.322 | | Note 3 |
| | Wy | | 0.312 | 0.327 | 0.342 | | |
| | Rx | | 0.609 | 0.624 | 0.639 | | |
| | Ry | | 0.316 | 0.331 | 0.346 | | |
| | Gx | | 0.281 | 0.296 | 0.311 | | |
| | Gy | | 0.562 | 0.577 | 0.592 | | |
| | Bx | | 0.128 | 0.143 | 0.158 | | |
| | By | | 0.094 | 0.109 | 0.124 | | |
| NTSC | | | 57% | 60% | - | | Note 3 |
| Cross talk | Ct | | - | - | 2% | | Note 9 |
| Transmittance | Trans | | - | 5.5% | - | | Note 4 |
| Luminous | L | Viewing normal angle | -- | 228 | -- | Cd/m ² | |

Without touch panel

| Item | Symbol | Condition | Specification | | | Unit | Remark |
|---------------|--------|----------------------|---------------|------|------|-------------------|------------|
| | | | Min. | Typ. | Max. | | |
| Viewing angle | Top | $CR \geq 10$ | - | 50 | - | Deg. | Note 2,6,7 |
| | Bottom | $CR \geq 10$ | - | 40 | - | | |
| | Left | $CR \geq 10$ | - | 60 | - | | |
| | Right | $CR \geq 10$ | - | 60 | - | | |
| Luminous | L | Viewing normal angle | --- | 265 | -- | Cd/m ² | |

Note 1: Ambient temperature = 25°C.

Note 2: To be measured with a viewing cone of 2° by Topcon luminance meter BM-5A.


Note 3: To be measured with Otsuta chromaticity meter LCF-2100M, CF only measure under C light simulation.

Note 4: CTC shipping status is cell without polarizer. Transmittance of Specification is cell with polarizer.

The tolerance of Transmittance is $\pm 10\%$.

Note 5: Definition of response time:

The output signals of TRD-100 are measured when the input signals are changed to “White” (falling time) and from “White” to “Black” (rising time), respectively. The interval is between the 10% and 90% of amplitudes. Refer to figure as below.




Note 6: Definition of contrast ratio:


Contrast ratio is calculated by the following formula.

$$\text{Contrast ratio (CR)} = \frac{\text{Brightness on the "white" state}}{\text{Brightness on the "black" state}}$$


Note 7: Definition of viewing angle



Note 8: Optical characteristic measurement setup.



Note 9:



$1 LA-LA' / LA \times 100\% = 2\% \text{ max.}$, LA and LA' are brightness at location A and A'.

$1 LB-LB' / LB \times 100\% = 2\% \text{ max.}$, LB and LB' are brightness at location B and B'.

9 Touch Panel specifications

| ITEM | VALUE | | | UNIT | REMARK |
|-----------------------|-----------|-----|--------|------------|---------------------------|
| | Min | Typ | Max | | |
| Linearity | - | - | 1.5 | % | Analog X and Y directions |
| Terminal Resistance | 200 | - | 500 | Ω | x |
| | 500 | - | 950 | | y |
| Insulation Resistance | 20 | - | - | M Ω | DC 25V |
| Voltage | - | 3 | 10 | V | DC |
| Chattering | - | - | 10 | ms | 100k Ω pull-up |
| Transparency | 80 | - | - | % | - |
| Operation Force | - | - | 100 | g | - |
| Endurance | 1,000,000 | - | - | Touches | 100g Operation Force |
| | - | - | 30,000 | Slides | |
| Surface Hardness | 3 | - | - | H | - |

10 RELIABILITY TEST



| NO. | TEST ITEM | TEST CONDITION | INSPECTION AFTER TEST |
|-----|----------------------------|---|--|
| 1 | High Temperature Storage | 80±2°C/96 hours | Inspection after 2~4 hours storage at room temperature and humidity. The condensation is not accepted. The sample shall be free from defects: 1. Air bubble in the LCD 2. Seal leak 3. Non-display 4. Missing segments 5. Glass crack |
| 2 | Low Temperature Storage | -30±2°C/96 hours | |
| 3 | High Temperature Operating | 70±2°C/96 hours | |
| 4 | Low Temperature Operating | -20±2°C/96 hours | |
| 5 | Temperature Cycle | -30±2°C ~ 25~ 80± 2°C × 10 cycles (30 min.) (5min.) (30min.) | |
| 6 | Damp Proof Test | 60°C ±5°C × 90%RH/96 hours | |

| | | | |
|----|------------------------------|--|--|
| 7 | Vibration Test | Frequency 10Hz~55Hz Stroke: 1.5mm Sweep: 10Hz~150 Hz~10Hz 2 hours For each direction of X, Y, Z | |
| 8 | Shock Test | Half-sine, wave, 300m/s | |
| 9 | Packing Drop Test | Height: 80 cm 1 corner, concrete floor | |
| 10 | Electrostatic Discharge Test | C=150pF, R=330 Ω Air: ±8KV 150pF/330Ω 30 times Contact: ±4KV,20 times | |


11 Inspection standards



11.1 Visual inspection criterion in cosmetic

11.1.1 Glass defect

| NO. | Defect | Criteria | Remark |
|-----|------------------|--------------------------|--|
| 1 | Dimension(Minor) | By engineering diagram |  |
| 2 | Cracks(Major) | Extensive crack [Reject] |  |

11.1.2 LCM appearance defect

| NO. | Defect | Criteria | | Remark |
|-----|-------------------|---|-----------------|---|
| | | Spec | Permissible Qty | |
| 1 | Round type(Minor) | $\phi \leq 0.1\text{mm}$ | Disregard | 1. $\phi = (W+L)/2$, L:Length,W=Width 2.Disregard if out of A.A  |
| | | $0.1\text{mm} < \phi \leq 0.2\text{mm}$ | 3 | |
| | | $\phi > 0.2\text{mm}$ | 0 | |
| 2 | Line type(Minor) | $W \leq 0.03\text{mm}$ | Disregard | 1. L:Length,W=Width 2.Disregard if out of A.A |
| | | $L \leq 3.0\text{mm}$ and $0.03\text{mm} < W \leq 0.05\text{mm}$ | 2 | |

| | | | | |
|---|-----------------------|---|-----------|---|
| | | $L \leq 3.0\text{mm}$ and $0.05\text{mm} < W \leq 0.1\text{mm}$ | 1 |  |
| | | $W > 0.10\text{mm}$ or $L > 3.0\text{mm}$ | 0 | |
| 3 | Polarizer dent(Minor) | $\phi \leq 0.2\text{mm}$ | Disregard | <p>1. $\phi = (W+L)/2$, L:Length, W=Width 2. Disregard if out of A.A</p>  |
| | | $0.2\text{mm} < \phi \leq 0.3\text{mm}$ | 2 | |
| | | $0.3\text{mm} < \phi \leq 0.5\text{mm}$ | 1 | |
| | | $\phi > 0.5\text{mm}$ | 0 | |

11.1.3 FPC

| NO. | Defect | Criteria | Remark |
|-----|-----------------------|-------------------------|--------|
| 1 | Copper peeling(Minor) | Copper peeling [Reject] | |
| 2 | Damaged | Damaged[Reject] | |

11.1.4 Black tape


| NO. | Defect | Criteria | Remark |
|-----|----------------------|------------------------|--------|
| 1 | Shift(Minor) | IC exposed [Reject] | |
| 2 | No black tape(Minor) | No black tape [Reject] | |



11.1.5 Silicon

| NO. | Defect | Criteria | Remark |
|-----|---------------------------|----------------------|--------|
| 1 | Amount of silicon (Minor) | ITO exposed [Reject] | |


11.1.6 Touch Panel

| Defect | Criteria | Remark |
|----------|---|--------|
| TP shift | Click on the TP, the distance between the show position and click position > 1.5mm [Reject] | |

| | | | |
|---|--------------------|----------------|--|
| TP Circle, Dent Dot, Bubble MI | Size(mm) | Accessible QTY |  |
| | $D \leq 0.20$ | Access | |
| | $0.2 < D \leq 0.3$ | 2 | |
| | $0.3 < D \leq 0.5$ | 1 | |
| | $D > 0.5$ | 0 | |

| | | |
|--|---|---|
| <p>TP Ripple MI</p> | <p>1.(Figure A): Ripple D>5mm [Reject] 2.(Figure B): Ripple area<1/7 TP area and not impact fonts display effect [Access]</p>  |  <p>A</p>  <p>B</p> |
| <p>Remark: Tear up the protective film to inspect. The distance of two dirt must>10mm; The white dot found in manufacture is conformity to 0.1mm, if >0.1mm [Reject]</p> | | |

11.2 Visual inspection criterion in electrical display

| NO. | Defect | Criteria | | Remark |
|-----|--------------------------------|--|-----------------|---|
| | | Spec. | Permissible Qty | |
| 1 | No display (Major) | Not allowed | | |
| 2 | Missing line (Major) | Not allowed | | |
| 3 | Darker or lighter Line (Major) | Not allowed | | |
| 4 | Weak line(Major) | By limited sample | | |
| 5 | Bright / Dark point (Minor) | Bright point | 1 | 1:1 sub-pixel: 1R or 1G or 1B 2:Point defect area 1/2 sub pixel. |
| | | Dark point | 2 | |
| 6 | Round type (Minor) | $\phi \leq 0.1\text{mm}$ | Disregard | 1. $\phi = (W+L)/2$, L:Length,W=Width 2.Disregard if out of A.A  |
| | | $0.1 < \phi \leq 0.2$ | 3 | |
| | | $\phi > 0.2\text{mm}$ | 0 | |
| | Line type (Minor) | $W \leq 0.03\text{mm}$ | Disregard | 1. L:Length,W=Width 2.Disregard if out of A.A |
| | | $L \leq 3.0\text{mm}$ and $0.03\text{mm} < W \leq 0.05\text{mm}$ | 2 | |
| | | $L \leq 3.0\text{mm}$ and $0.05\text{mm} < W \leq 0.1\text{mm}$ | 1 | |

| | | | | |
|--|--------------|---|---|--|
| | | $W > 0.10\text{mm}$ or $L > 3.0\text{mm}$ | 0 | |
| | Mura (Minor) | By 5% ND filter invisible | | |

11.3 Others

1. Issues that are not defined in this document shall be discussed and agreed with both parties. (Customer and supplier)
2. Unless otherwise agreed upon in writing, the criteria shall be applied to both parties. (Customer and supplier)

12 Suggestions for using LCD modules

12.1 Handling of LCM

1. The LCD screen is made of glass. Don't give excessive external shock, or drop from a high place.
2. If the LCD screen is damaged and the liquid crystal leaks out, do not lick and swallow. When the liquid is attach to your hand, skin, cloth etc, wash it off by using soap and water thoroughly and immediately.
3. Don't apply excessive force on the surface of the LCM.
4. If the surface is contaminated, clean it with soft cloth. If the LCM is severely contaminated, use Isopropyl alcohol/Ethyl alcohol to clean. Other solvents may damage the polarizer. The following solvents is especially prohibited: water , ketone Aromatic solvents etc.
5. Exercise care to minimize corrosion of the electrode. Corrosion of the electrodes is accelerated by water droplets, moisture condensation or a current flow in a high-humidity environment.
6. Install the LCD Module by using the mounting holes. When mounting the LCD module make sure it is free of twisting, warping and distortion. In particular, do not forcibly pull or bend the I/O cable or the backlight cable.
7. Don't disassemble the LCM.
8. To prevent destruction of the elements by static electricity, be careful to maintain an optimum work environment.
 - Be sure to ground the body when handling the LCD modules.
 - Tools required for assembling, such as soldering irons, must be properly grounded.
 - To reduce the amount of static electricity generated, do not conduct assembling and other work under dry conditions.
 - The LCD module is coated with a film to protect the display surface. Exercise care when peeling

off this protective film since static electricity may be generated.

9. Do not alter, modify or change the the shape of the tab on the metal frame.
10. Do not make extra holes on the printed circuit board, modify its shape or change the positions of components to be attached.
11. Do not damage or modify the pattern writing on the printed circuit board.
12. Absolutely do not modify the zebra rubber strip (conductive rubber) or heat seal connector
13. Except for soldering the interface, do not make any alterations or modifications with a soldering iron.
14. Do not drop, bend or twist LCM.

12.2 Storage

1. Store in an ambient temperature of 5 to 45 C, and in a relative humidity of 40% to 60%. Don't expose to sunlight or fluorescent light.
2. Storage in a clean environment, free from dust, active gas, and solvent.
3. Store in antistatic container.

Packing

| PARAMETER | Specification | Unit |
|--------------------------------|--------------------------|------|
| Outside box | 390(L) x 350(W) x 480(H) | mm |
| Inside pearl wool box | 330(L)x185(W)x110(H) | mm |
| Product quantity of Inside box | 64 | pcs |
| Total product quantity | 64*8=512 | pcs |
| Total weight | 14.0±0.5 | Kg |

