



PIN	DESCRIPTION
1	GND
2	VCC
3	IDVCC
4	NCCSDD
5	SDA
6	SCL
7	CS
8	RESET
9	DB15
10	DB14
11	DB13
12	DB12
13	DB11
14	DB10
15	DB9
16	DB8
17	DB7
18	DB6
19	DB5
20	DB4
21	DB3
22	DB2
23	DB1
24	DB0
25	DE
26	PCLK
27	HSYNC
28	VSYNC
29	LEDA
30	LEDK
31	NC
32	NC
33	NC

LCD Type	3.46" TFT, Transmissive, Normally black, ips
Resolution	340(RGB)*800
View Direction	All O'CLOCK
Driver IC	ST7701S
Color Depth	16.7M
Interface Types	TTL(RGB24-bit)
Operating voltage	3.3V
TP/Lens	Without
Backlight LEDs	10 LEDs, 20mA, 21.7V
Surface luminance	300 cd/m2
Operating temperature	-20 °C ~ 70 °C
Storage Temperature	-30 °C ~ 80 °C
Storage Humidity	60% ~ 90% max

" " Need to pay attention to		the key size with *		东莞市一众显示科技有限公司 DONG GUAN TEAM SOURCE DISPLAY TECH. CO, LTD.	
版本 (Version)	变更记录 (Change History)	日期 (Date)	视角 (View):	比例 (Proportion):	1 : 1
V1			单位 (Unit):	MM	页面 (Page): 1 / 1
V2			产品型号 (Product Type):	TST035WVBS-51	设计 (DESIGN): Aron
			图纸版本 (Version):	V1	审核 (AUDITING):
					批准 (APPROVED):
					2018.10.26