



LCD Type	5.0" TFT, Transmissive, Normally white, TN
Resolution	800(RGB)*480
View Direction	12 O'CLOCK
Driver IC	ILI5480*1/ILI6123H*2
Color Depth	16.7M
Interface Types	TTL(RGB24-bit)
Operating voltage	3.3V
TP/Lens	With CTP(FT3316)
Backlight LEDs	12 LEDs, 40mA, 18.6V
Surface luminance	300 cd/m2
Operating temperature	-20 °C ~ 70 °C
Storage Temperature	-30 °C ~ 80 °C
Storage Humidity	60% ~ 90% max

TP PIN ASSIGNMENT

1	GND
2	GND
3	RST
4	INT
5	SDA
6	SCL
7	VCC
8	VCC

PIN NAME	
1	VLED-
2	VLED+
3	GND
4	VDD
5	R0
6	R1
7	R2
8	R3
9	R4
10	R5
11	R6
12	R7
13	G0
14	G1
15	G2
16	G3
17	G4
18	G5
19	G6
20	G7
21	B0
22	B1
23	B2
24	B3
25	B4
26	B5
27	B6
28	B7
29	GND
30	DCLK
31	DISP
32	HSYNC
33	VSYNC
34	DE
35	NC
36	GND
37	XR
38	YD
39	XL
40	YL

Need to pay attention to the key size with *

版本 (Version)	变更记录 (Change History)	日期 (Date)	视角 (View):	比例 (Proportion):	设计 (DESIGN)	审核 (AUDITING)	批准 (APPROVED)
V1			单位 (Unit):	页 面 (Page):	Ar-on	Penix	
V2			产品型号 (Product Type):	TST050WVHT-11C	2017.9.19	2017.9.19	

东莞市一众显示科技有限公司
DONG GUAN TEAM SOURCE DISPLAY TECH. CO, LTD.